

## DS-2CD2122FWD-I (W) (S) 2MP WDR Fixed Dome Network Camera



- Up to 2 megapixel high resolution
- Full HD1080p video
- Dual video streams
- 4mm/6mm fixed lens
- 120dB Wide Dynamic Range
- 3D Digital Noise Reduction
- 3-axis adjustment
- DC12V & PoE
- Support H.264+
- Up to 30m IR range
- IP66 weather-proof protection
- IK08(-W model)/IK10(non -W model)
- -S: Audio/Alarm IO
- -W: Built-in Wi-Fi

### Camera Accessories



Inclined ceiling mount  
DS-1259ZJ



Wall mount  
DS-1272ZJ-110



Wall mount + Junction Box  
DS-1272ZJ-110B



Pendant mount  
DS-1271ZJ-110B



Junction Box  
DS-1280ZJ-DM18



Corner mount  
DS-1276ZJ



Vertical Pole mount  
DS-1275ZJ



Rain-proof Cap  
DS-1250ZJ



# DS-2CD2122FWD-I (W)(S) 2MP WDR Fixed Dome Network Camera



## Specification

<b>Camera</b>	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR
Shutter Speed	1/3 s to 1/10,000 s
Lens	4mm, 6mm @ F2.0
Lens Mount	M12
Day &Night	IR cut filter with auto switch
DNR	3D DNR
Wide Dynamic Range	120dB
P&T rotation	Pan: 0° ~ 355°, Tilt: 0° ~ 75°, Rotation: 0° ~ 355°
<b>Compression Standard</b>	
Video Compression	H.264 / MJPEG/H.264+
H.264 Type	Main Profile
Video Bit Rate	32 Kbps ~ 16 Mbps
Dual streams	Support
<b>Image</b>	
Max. Resolution	1920 × 1080
Frame Rate	50Hz: 25fps (1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps (1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
BLC	Support, zone configurable
ROI Codec	Support
<b>Network</b>	
Network Storage	NAS (Support NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General	One-key reset, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
<b>Interface</b>	
Communication Interface	1 RJ45 10M/100M Ethernet port
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
Alarm interface	1x alarm I/O *only for -S models
Audio interface	1x audio I/O *only for -S models
Reset	Yes

# DS-2CD2122FWD-I (W)(S) 2MP WDR Fixed Dome Network Camera



## Wi-Fi \* only for -W models

Wireless Standards	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	20/40MHz Support
Protocols	802.11b: CCK, QPSK, BPSK, 802.11g/n: OFDM
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Transmit Output Power	11b: 17±1.5dBm @ 11Mbps 11g: 14±1.5dBm @ 54Mbps 11n: 12.5±1.5dBm
Reception Sensitivity	11b: -90dBm @ 11Mbps (Typical) 11g: -75dBm @ 54Mbps (Typical) 11n: -74dBm (Typical)
Transfer Rates	11b: 11Mbps, 11g: 54Mbps, 11n: up to 150Mbps
Wireless Range	50 meters *The performance varies based on actual environment.

## General

Operating Conditions	-30 °C – 60 °C (-22 °F – 140 °F), Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%, PoE (802.3af)
Power Consumption	Max. 5W Max. 9W with pan and tilt
IR Range	Approx. 30 meters
Ingress Protection	IP66
Impact Protection	IK08(-W model)/IK10(non -W model)
Dimensions	Φ111 × 82 (4.4" × 3.2")
Weight	500g (1.1lbs)

## Order Models

DS-2CD2122FWD-I, DS-2CD2122FWD-IS, DS-2CD2122FWD-IW, DS-2CD2122FWD-IWS

-S: Audio/Alarm IO, -W: Built-in Wi-Fi

## Dimensions

